


LIBERTY SERIES - LL12

Progressive Cavity Pump



LL3

LL4

LL2

0.40 GPM

Features

- Modular Design
- Maintenance Free
- Easy Assembly/Disassembly
- Simple Pin Joint Design
- Non-Pulsating Low Shear
- NPT Discharge Connection

Materials

- Rotor: Tool Steel & Stainless Steel, Chrome-Plated
- **Stator:** *Buna, Rubber, Viton™, EPDM*

Motor: 3, 5, 7.5, 10, 15, 20, and 25 hp

- Inlet: 8"
- Outlet: 6"
- Bases: Carbon Steel and Stainless Steel



Pump Description

The Liberty LL12 Progressive Cavity Pump is an ideal industrial-sized heavy-duty pumping unit for abrasive pumping applications like thickened grease, scum and slurries. The Liberty LL12 Series PC Pump is a standard flanged pump manufactured with cast iron or 316 stainless steel casings and designed in 1, 2, and 3 stages for 75, 150 and 225 psi discharge pressures.

The pump unit is a modular design with simple hardened pinned joint drive assembly. Rotors are typically hardned tool steel or 316 stainless steel with a hard chrome plating for long life in abrasive and erosive applications. All other wetted parts are either carbon steel or 316 stainless steel for added durability.

Stators are available in many elastomer materials such as buna, natural rubber, epdm and viton. The standard seal design is a set of gland packing with Lantern Ring and Flush Connections. Mechanical seal options are readily available. The Liberty unit is a low-cost, maintenance free, dependable drop-in replacement pump which will give you the service you need at a price you can afford.

The Liberty LL12 Progressive Cavity Pump parts are direct aftermarket replacements that work with the Moyno[™] L12 Series, Tarby[™] TL12 Series and Continental[™] CL12 Series.*

Contact a Liberty Process representative today for more information about the LL12 Series.

LL8

LL6



P: 847.640.7867 F: 847.640.7855

LL10

2525 Clearbrook Drive Arlington Heights, IL 60005

LL10H

LL12

LL12H




LIBERTY SERIES - ILL12

Progressive Cavity Pump

Performance Curves

RPM	100	200	300	400	500	600
NPSH REQ'D	1.2	2.3	3.4	5.6	8.4	11.2
MIN. HP	3	5	5	7-1/2	10	10



DIFFERENTIAL PRESSURE (PSI)

1 Stage Pump



P: 847.640.7867 F: 847.640.7855 2525 Clearbrook Drive Arlington Heights, IL 60005




LIBERTY SERIES - 2LL12

Progressive Cavity Pump

Performance Curves

RPM	100	200	300	400	500	600
NPSH REQ'D	1.2	2.3	3.4	5.6	8.4	11.2
MIN. HP	5	7-1/2	10	15	15	20



DIFFERENTIAL PRESSURE (PSI)

2 Stage Pump



P: 847.640.7867 F: 847.640.7855 2525 Clearbrook Drive Arlington Heights, IL 60005




LIBERTY SERIES - 3LL12

Progressive Cavity Pump

Performance Curves

RPM	100	200	300	400	500	600
NPSH REQ'D	1.2	2.3	3.4	5.6	8.4	11.2
MIN. HP	5	10	15	15	20	25



DIFFERENTIAL PRESSURE (PSI)

3 Stage Pump




P: 847.640.7867 F: 847.640.7855 2525 Clearbrook Drive Arlington Heights, IL 60005



LIBERTY SERIES - ILL12

Progressive Cavity Pump

Dimensional Drawings




	Net weight
	≈ lbs.
BACK TO TOP ALL DIMN: Inches	880
P: 847.640.7867 2525 Clearbrook Drive Arlington	′F: 847.640.7855 Heights, IL 60005



LIBERTY SERIES - 2LL12

Progressive Cavity Pump

Dimensional Drawings



	Net weight
	≈ lbs.
ALL DIMN: Inches	1075
P: 847.640.7867 2525 Clearbrook Drive Arlington P	


www.libertyprocess.com



LIBERTY SERIES - 3LL12

Progressive Cavity Pump

Dimensional Drawings



	Net weight
	≈ lbs.
BACK TO TOP ALL DIMN: Inches	1200
Bit Stage Pump P: 847.640.7867 2525 Clearbrook Drive Arlington	F: 847.640.7855 Heights, IL 60005

www.libertyprocess.com